

Two Page Stata

Andrew Grogan-Kaylor

July 05, 2018

An introduction to Stata¹ in 2 pages.² Commands³ that you actually type into Stata⁴ are represented in monospace font. `x` and `y` refer to variables in your data. The treatment here is intended to be extremely brief, in order to create a kind of “cheat sheet” that can be presented in 2 pages. More documentation on any command is available in the printed or PDF Stata manuals, or by typing `help command`.

1 Get Acquainted With Your Data⁵

`lookfor` allows you to find variables that contain a specified keyword. This is especially useful in large data sets with many variables. Often abbreviated keywords are the most helpful. e.g. to find a poverty variable, type `lookfor pov`.

`describe` tells you about the contents of a specific variable. E.g. `describe x y`. `describe, short` will tell you very basic things about your data, including the number of observations in the data set, and the size of your data file.

2 Process Your Data⁶

`recode x (oldvalue = newvalue)`, `generate(z)` will recode a variable into a new variable, often a good idea.

`recode _all (-99/-1 = .)` will recode all negative numbers from -99 to -1 to missing for all variables in your data. `recode x (7/9 = .)` changes 7 through 9 to be missing for `x`. Indeed, `recode` will change specific values in your data to anything you want, not just missing values.

It is often convenient to `rename` your variables so that the variables have more intuitively understandable names e.g. `rename x depression`.

You can create new variables out of old variables using `generate newvar = expression` e.g. `generate newvar = oldvar1 + oldvar2`.⁷

It is sometimes useful to sort your data. `sort x` will sort your data by the values of `x`.

3 Descriptive Statistics

`summarize` gives you basic descriptive statistics for a variable, such as the mean (average). Especially useful for continuous variables. E.g. `summarize x y` or `summarize x y, detail`.

¹ [Share on Twitter](#)

² Comments, questions and corrections most welcome and may be sent to: [Andrew Grogan-Kaylor @ agrogan@umich.edu](mailto:Andrew.Grogan-Kaylor@agroganweb.umich.edu). This document available on the web @ <https://agroganweb.wordpress.com/stata-resources/>

³ The Stata interface makes it extremely easy to do rapid interactive data analysis. Hit **PAGE-UP** to recall the most recent command, which you can then quickly edit and resubmit. The general idea of most Stata commands is command variables, options. Often it is not necessary to use any options since the authors of Stata have done such a good job of thinking about the defaults.

⁴ Use the **DO FILE EDITOR** to save Stata commands that you want to use again, and to create an “audit trail” of your work so that your workflow is documented and replicable. `log using filename`, `replace` will save a log file of your results. `log close` closes the log file.

⁵ `codebook x y` will produce a nicely formatted codebook of selected variables, which is especially useful if you have added variable labels with the `label variable` command. `codebook` is especially useful for seeing how numerical values are associated with value labels. `codebook` by itself will list every variable in your data and generate a lot of [probably too much] output.

⁶ Data with missing values, often represented as negative numbers (e.g. -99, -9, -8) need to be recoded so that the missing values are represented as a missing value character (“.”) that Stata knows to exclude from calculations.

⁷ `alpha oldvar1 oldvar2` will calculate Cronbach's alpha from this scale.

`tabulate` gives you a frequency distribution for your variable. Especially useful for categorical variables. e.g. `tabulate x`.

4 Bivariate Statistics⁸

Tabulating two categorical variables together gives you a cross-tabulation of those variables, e.g. `tabulate x y, row col chi2`

`pwcorr x y, sig` gives you the pairwise correlation of two continuous variables.

5 Multivariate Statistics⁹

`regress y x` regresses y on x .¹⁰

`regress y x z` regresses y on x and z .¹¹ `regress y x i.z` regresses y on x and z , treating x as continuous and z as a set of categorical indicator variables.

6 Graphing¹²

`histogram x` will give you a nice display of one variable. `histogram x, by(y)` may be useful for comparing the distributions of two variables over the categories of y .

`histogram x, percent` will scale the y -axis more intuitively in terms of percentages. `histogram x, discrete`¹³ gives a nicer display for categorical variables.

`twoway scatter y x` gives you a twoway scatterplot of your data.

`twoway lfit y x` will give you a linear fit graph. The two syntaxes may be combined e.g. `twoway (scatter y x)(lfit y x)`.

`graph bar x, over(y)` is useful for creating a bar graph of a continuous or categorical variable graphed across the categories of a categorical variable.

7 by:

In many cases you may want to look at the results of some calculation for x , or x and y over a third variable z . In such cases the `by:` syntax will be especially useful. For example to look at the correlation of x and y over different values of z .

`sort z by z: pwcorr x y, sig`

⁸ `oneway continuous_var categorical_var, tabulate` gives you a oneway ANOVA of a continuous variable over a categorical factor.

⁹ Stata's factor variables allow one to generate interactions and indicator variables on the fly, but again are beyond the purview of this guide.)

¹⁰ After running many multivariate models `estat summarize` will give you simple descriptive statistics for the specific sample used in that particular analysis.

¹¹ Other regression commands follow a very similar format: `command y x z` but are beyond the purview of this 2 page guide.

¹² For all graphs, options after a `"` will be helpful in titling your graph e.g. `twoway lfit y x, title(".") xtitle(".") ytitle(".")`

¹³ The `percent` and `discrete` options can be combined.