

Composite Hypar Structural System

**THOMAS F. MORIARTY
JOSEPH A. KERSAVAGE
PETER VON BUELOW**

**UNIVERSITY OF TENNESSEE
310 PERKINS HALL
KNOXVILLE, TN 37996 - 2030**

JUNE 1985

**FINAL REPORT
DECEMBER 1982 - SEPTEMBER 1984**

DISTRIBUTION LIMITED TO U.S. GOVERNMENT AGENCIES ONLY. THIS REPORT DOCUMENTS TEST EVALUATION. DISTRIBUTION LIMITATION APPLIED JUNE 1985. OTHER REQUESTS FOR THIS DOCUMENT MUST BE REFERRED TO THE AIR FORCE ENGINEERING AND SERVICES CENTER (AFESC/RDCS), TYNDALL AIR FORCE BASE, FLORIDA 32403.

WARNING

INFORMATION SUBJECT TO EXPORT CONTROL LAWS
THIS DOCUMENT MAY CONTAIN INFORMATION SUBJECT TO THE INTERNATIONAL TRAFFIC IN ARMS REGULATION (ITAR) OR THE EXPORT ADMINISTRATION REGULATION (EAR) OF 1979 WHICH MAY NOT BE EXPORTED, RELEASED, OR DISCLOSED TO FOREIGN NATIONALS INSIDE OR OUTSIDE THE UNITED STATES WITHOUT FIRST OBTAINING AN EXPORT LICENSE. A VIOLATION OF THE ITAR OR EAR MAY BE SUBJECT TO A PENALTY OF UP TO 10 YEARS IMPRISONMENT AND A FINE OF \$100,000 UNDER 22 U.S.C. 2778 OR SECTION 2410 OF THE EXPORT ADMINISTRATION ACT OF 1979. INCLUDE THIS NOTICE WITH ANY REPRODUCED PORTION OF THIS DOCUMENT.



**ENGINEERING & SERVICES LABORATORY
AIR FORCE ENGINEERING & SERVICES CENTER
TYNDALL AIR FORCE BASE, FLORIDA 32403**

NOTICE

**Please do not request copies of this report from
HQ AFESC/RD (Engineering and Services Laboratory).**

Additional copies may be purchased from:

**Defense Technical Information Center
Cameron Station
Alexandria, Virginia 22314**

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED		1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION/AVAILABILITY OF REPORT Distribution is limited to U.S. Government Agencies only. This report documents test Evaluation. Distribution limitation applied June 1985. (Cont.)	
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE		4. PERFORMING ORGANIZATION REPORT NUMBER(S)	
4. PERFORMING ORGANIZATION REPORT NUMBER(S)		5. MONITORING ORGANIZATION REPORT NUMBER(S) ESL-TR-85-07	
6a. NAME OF PERFORMING ORGANIZATION University of Tennessee	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION HQ Air Force Engineering and Services Center	
6c. ADDRESS (City, State and ZIP Code) 310 Perkins Hall Knoxville, TN 37996-2030		7b. ADDRESS (City, State and ZIP Code) Engineering and Services Laboratory (RDCS) Tyndall AFB FL 32403	
8a. NAME OF FUNDING/SPONSORING ORGANIZATION HQ Air Force Eng & Svcs Center	8b. OFFICE SYMBOL (If applicable) RDCS	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER F08635-83-C-0057	
8c. ADDRESS (City, State and ZIP Code) Engineering and Services Laboratory Tyndall AFB, FL 32403		10. SOURCE OF FUNDING NOS.	
11. TITLE (Include Security Classification) Composite Hypar Structural System		PROGRAM ELEMENT NO. 62601F	PROJECT NO. 2673
		TASK NO. -	WORK UNIT NO. 0021
12. PERSONAL AUTHOR(S) Thomas F. Moriarty, Joseph A. Kersavage, Peter Von Buelow			
13a. TYPE OF REPORT Final Report	13b. TIME COVERED FROM <u>Dec 82</u> TO <u>Sep 84</u>	14. DATE OF REPORT (Yr., Mo., Day) 1985 June	15. PAGE COUNT 74
16. SUPPLEMENTARY NOTATION Availability of this report is specified on reverse of front cover.			
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB. GR.	
13	13	Composite Structures Hardened Structures Shells (Structural Dynamic Loads Explosive Effects Forms)	
13	02	Impulse Loading Underground Structures Vulnerability	
19. ABSTRACT (Continue on reverse if necessary and identify by block number) A new underground shelter to resist explosions of 500 pounds (226.8 kg) of TNT is currently under development. This shelter uses prefabricated hyperbolic paraboloids with a coating of reinforced concrete and asphalt composite. The new design reduces the required structural wall thickness from 31.7 inches (0.805 meters) needed in the conventional concrete barrel vault design, or from 37.4 inches (0.950 meters) needed in the conventional concrete rectangular box design to resist localized effects of conventional weapons blast, to only 6 inches (0.152 meters). The HYPAR shelter also has the following design advantages: rapid deployment; ease and simplicity of construction; elimination of formwork; modular designed interconnecting shelters; ability to shock isolate the interior ground slab; large foundation footprint for poor soil conditions; exceptional resistance to "floating" in high water table applications; excellent integral waterproofing; elimination of internal destructive spalling; excellent sealing against chemical or biological agents even if the main structure is fractured; ability to function as an economical, permanent multiuse space; overall economic advantage.			
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input checked="" type="checkbox"/> DTIC USERS <input type="checkbox"/>		21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED	
22a. NAME OF RESPONSIBLE INDIVIDUAL Lt THOMAS J. HILFERTY		22b. TELEPHONE NUMBER (Include Area Code) (904) 283-6278	22c. OFFICE SYMBOL RDCS